



PermaShield™ Fuel Resistant Gasket Dressing & Flange Sealant



Resistant to all automotive fuels. Non-Hardening & Non-Setting.



Find out more at
www.permatex.com.au



PermaShield™ Fuel Resistant Gasket Dressing & Flange Sealant

Product Description

Specially formulated for superior fluid resistance, this polyester urethane based gasketing compound withstands extreme temperature changes without hardening. Its non-setting, non-hardening character remains tacky even with rapid changes in temperature, enabling repeated assembly and disassembly of parts. Suitable as either a gasket maker or dressing, PermaShield™ seals surface imperfections between metal parts and is ideal in high performance applications. With an operating temperature range of -60° to 500°F (-50° to 260°C), this compound resists common engine fluids, including oil, gasoline, ethanol, water and anti-freeze and prevents contamination from moisture and dust.

Directions for Use

1. Clean and dry surfaces.
2. Apply thin film or bead to both surfaces.
3. Allow ample drying time to completely evaporate solvent.
4. Assemble and torque to manufacturer s specifications. Seals instantly. May return equipment to service immediately. Replace cap after use. Store below 100°F (38°C).

Typical Applications

- Axle assemblies
- Hydraulic parts
- Differential covers
- Oil pans (cast)
- Water pumps
- Bearing caps/brackets
- Gearboxes
- Hydraulic equipment covers
- Intake manifold gaskets
- Valve cover gaskets

Product Code	Size	Product Barcode	Ctn. Qty.	Carton Barcode
85420	59ml Tube	686226854209	6	30686226854200

Our Brands

