

Castrol RX Gas

For long and healthy engine life

Description

Castrol RX Gas has a special low ash formulation developed to provide complete protection for gas fuelled engines, including liquid and compressed natural gas.

Application

Developed for gas powered commercial vehicle engines, particularly MAN.

Advantages

Long Term Engine Durability

Castrol RX Gas offers a high level of long term protection including:

- **Protection against deposit formation.** Gas fuelled engines are sensitive to the formation of deposits on the piston crown area, which leads to uncontrolled ignition and consequent loss in engine performance and if unchecked, to complete engine failure. **Castrol RX Gas** has a special low ash-forming formulation to minimise deposit build-up, this ensures efficient engine operation and longer engine life.
- **Protection against wear.** **Castrol RX Gas** contains advanced anti-wear additives to protect against premature engine failure from wear, so reducing maintenance costs.

Typical Characteristics

Test	Method	Unit	Typical Characteristic
SAE Grade		-	15W-40
KV @40 °C	ASTM D445	cSt	102
KV @100 °C	ASTM D445	cSt	13.7
CCS @-20 °C	ASTM 5293	cP	6800
Pour Point	ASTM D97	°C	-30
Flash Point (COC)	ASTM D92	°C	236
Sulphated Ash	D874	% Mass	0.8
Total Base Number	ASTM D2896	mg/KOH/g	7.0

The above data is typical and does not constitute a specification.

Performance Levels

This advanced lubricant should be used where the following requirements are cited:

- MAN M 3271-1
- DAF HP Gas

Product Removal

Bare Metal Surfaces: Remove with Castrol solvent cleaners or water based degreasers.

Hand Cleaning: Use any of the Castrol range of hand cleaners; e.g. CareClean Plus.

Other Surfaces: Contact your local Technical Advice Line on 1300 557 998.

Castrol RX Gas
RX Gas_468112_2013_11.docx replaces RX Gas_468112_2013_03
November 2013
Castrol RX Gas and the Castrol logo are trademarks of Castrol Limited, used under licence.

Castrol Australia Pty Limited, - ABN 87 008 459 407 GPO Box 5222, Melbourne VIC 3001
Technical Advice Line 1300 557 998 / Customer Service 1300 554 890
www.castrol.com.au

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See <http://www.msds.castrol.com.au/>. No responsibility is taken by either Castrol Australia Pty Limited, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.