

Castrol RX Mono 40

For long and healthy engine life

Description

Castrol RX Mono 40 is a heavy duty monograde medium ash engine oil formulated from highly refined mineral base oils.

Application

Castrol RX Mono 40 may be recommended for use in a wide variety of engines and transmissions. Castrol RX Mono 40 particularly suits fleet operators who favour monograde engine oils where a common oil is preferred for engine and powershift transmissions.

Some engine manufacturers, Gardner and International (tractors), prefer monograde engine oils. Many others allow monograde engine oils under suitable ambient conditions. Castrol RX Mono 40 is a versatile heavy duty engine oil that can be used where monograde API CF, SG engine oils are recommended. It is also recommended for transmissions where an SAE 40 monograde engine oil is specified.

Advantages

Castrol RX Mono 40 contains modern additives designed to provide excellent engine protection in a wide selection of petrol and diesel engines operating under varying climatic conditions, driving methods and engine loads, where lubricants of this quality are recommended by the OEM.

Typical Characteristics

Name	Method	Units	RX Mono 40
Density @ 15°C, relative	ASTM D4052	g/ml	0.894
Viscosity, Kinematic @ 100 °C	ASTM D445	mm ² /s	15.0
Flash Point, COC	ASTM D92	°C	252
Viscosity, Kinematic @ 40 °C	ASTM D445	mm ² /s	155
Viscosity Index	ASTM D2270	None	96
Ash, Sulphated	ASTM D874	% wt	0.9
Total Base Number, TBN	ASTM D2896	Mg KOH/g	7.1
Pour Point	ASTM D97	°C	-24

The above data is typical and does not constitute a specification.

Performance Levels

- API CF/SG
- MB – Approval 228.0

Product Removal

Bare Metal Surfaces: Remove with Castrol solvent cleaners or water based degreasers.

Hand Cleaning: Use any of the Castrol range of hand cleaners; e.g. CareClean Plus.

Other Surfaces: Contact your local Technical Advice Line on 1300 557 998.

Castrol RX Mono 40
Castrol RX Mono 40_468114_2013_11.docx replaces RX Mono 40_468114_2013_05
November 2013
Castrol RX and the Castrol logo are trademarks of Castrol Limited, used under licence.

Castrol Australia Pty Limited, - ABN 87 008 459 407 GPO Box 5222, Melbourne VIC 3001
Technical Advice Line 1300 557 998 / Customer Service 1300 554 890
www.castrol.com.au

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See <http://www.msds.castrol.com.au/>. No responsibility is taken by either Castrol Australia Pty Limited, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.